

Sliding shutters



COPYTRACER
Anti-counterfeit registration number



Improved air channels



Bottom clamp



Environment friendly



DX³ The Next Step.

Presenting, DX³, an international range of protection devices. Its revolutionary design supports all kind of installations thus giving a never before experience. With 10 patents and 13 new features, it defines the next step in the protection category.

New top clamp
for all tools



Technical
labelling area




F10A

Integrated label
holder



Black handle: circuit breakers
Grey handle: switches

Breaking capacity

- 16 kA 
- 25 kA 
- 36 kA 
- 50 kA 

Colour coded
handle with
ON/OFF
colour indication



DX³ MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

MCBs for AC applications till 63 A

10 kA ISI marked as per IS/IEC 60898-1 2002
 Integrated label holder
 Sliding bottom clamp
 Improved air channels
 Color coded On/Off indication on dolly
 Biconnect lower terminals
 IP 20 protected terminals
 Sliding shutters
 DC-80 V per pole - 1 kA

C Curve

Single pole 240/410 V

4085 80	0.5	1	396	1/10/120
4085 81	1	1	396	1/10/120
4085 83	2	1	396	1/10/120
4085 84	3	1	396	1/10/120
4085 85	4	1	396	1/10/120
4085 87	6	1	260	1/10/120
4085 90	10	1	260	1/10/120
4085 92	16	1	260	1/10/120
4085 93	20	1	260	1/10/120
4085 94	25	1	260	1/10/120
4085 95	32	1	260	1/10/120
4085 96	40	1	564	1/10/120
4085 97	50	1	564	1/10/120
4085 98	63	1	564	1/10/120



4085 90

Single pole + Neutral 240 V

4086 02	0.5	2	1076	1/5/60
4086 03	1	2	1076	1/5/60
4086 05	2	2	1076	1/5/60
4086 06	3	2	1076	1/5/60
4086 07	4	2	1076	1/5/60
4086 09	6	2	772	1/5/60
4086 12	10	2	772	1/5/60
4086 14	16	2	772	1/5/60
4086 15	20	2	772	1/5/60
4086 16	25	2	772	1/5/60
4086 17	32	2	772	1/5/60
4086 18	40	2	1242	1/5/60
4086 19	50	2	1242	1/5/60
4086 20	63	2	1242	1/5/60



4086 14

Double pole 415 V

4086 21	0.5	2	1076	1/40
4086 22	1	2	1076	1/40
4086 24	2	2	1076	1/40
4086 25	3	2	1076	1/40
4086 26	4	2	1076	1/40
4086 28	6	2	772	1/40
4086 31	10	2	772	1/40
4086 33	16	2	772	1/40
4086 34	20	2	772	1/40
4086 35	25	2	772	1/40
4086 36	32	2	772	1/40
4086 37	40	2	1242	1/40
4086 38	50	2	1242	1/40
4086 39	63	2	1242	1/40



4086 37

Triple pole 415 V

4086 43	0.5	3	1666	1/32
4086 44	1	3	1666	1/32
4086 46	2	3	1666	1/32
4086 47	3	3	1666	1/32
4086 48	4	3	1666	1/32
4086 50	6	3	1258	1/32
4086 53	10	3	1258	1/32
4086 55	16	3	1258	1/32
4086 56	20	3	1258	1/32
4086 57	25	3	1258	1/32
4086 58	32	3	1258	1/32
4086 59	40	3	1924	1/32
4086 60	50	3	1924	1/32
4086 61	63	3	1924	1/32



4086 55

DX³ MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Triple pole + Neutral 415 V

4086 65	0.5	4	2088	1/32
4086 66	1	4	2088	1/32
4086 68	2	4	2088	1/32
4086 69	3	4	2088	1/32
4086 70	4	4	2088	1/32
4086 72	6	4	1702	1/32
4086 75	10	4	1702	1/32
4086 77	16	4	1702	1/32
4086 78	20	4	1702	1/32
4086 79	25	4	1702	1/32
4086 80	32	4	1702	1/32
4086 81	40	4	2454	1/32
4086 82	50	4	2454	1/32
4086 83	63	4	2454	1/32



4086 77

Four pole 415 V

4086 84	0.5	4	2088	1/32
4086 85	1	4	2088	1/32
4086 87	2	4	2088	1/32
4086 88	3	4	2088	1/32
4086 89	4	4	2088	1/32
4086 91	6	4	1702	1/32
4086 94	10	4	1702	1/32
4086 96	16	4	1702	1/32
4086 97	20	4	1702	1/32
4086 98	25	4	1702	1/32
4086 99	32	4	1702	1/32
4087 00	40	4	2454	1/32
4087 01	50	4	2454	1/32
4087 02	63	4	2454	1/32



4086 94

D Curve

Single pole 240/415 V

4087 06	0.5	1	396	1/10/120
4087 07	1	1	396	1/10/120
4087 09	2	1	396	1/10/120
4087 10	3	1	396	1/10/120
4087 11	4	1	396	1/10/120
4087 12	6	1	332	1/10/120
4087 14	10	1	332	1/10/120
4087 16	16	1	332	1/10/120
4087 17	20	1	332	1/10/120
4087 18	25	1	332	1/10/120
4087 19	32	1	332	1/10/120
4087 20*	40	1	596	1/10/120
4087 21*	50	1	596	1/10/120
4087 22*	63	1	596	1/10/120



4087 19

Single pole + Neutral 240 V

4087 26	0.5	2	1076	1/5/60
4087 27	1	2	1076	1/5/60
4087 29	2	2	1076	1/5/60
4087 30	3	2	1076	1/5/60
4087 31	4	2	1076	1/5/60

Double pole 415 V

4087 32	0.5	2	1076	1/40
4087 33	1	2	1076	1/40
4087 35	2	2	1076	1/40
4087 36	3	2	1076	1/40
4087 37	4	2	1076	1/40
4087 38	6	2	796	1/40
4087 40	10	2	796	1/40
4087 42	16	2	796	1/40
4087 43	20	2	796	1/40
4087 44	25	2	796	1/40
4087 45	32	2	796	1/40
4087 46*	40	2	1288	1/40
4087 47*	50	2	1288	1/40
4087 48*	63	2	1288	1/40



4087 46

* MRP - Maximum Retail Price Inclusive of all taxes.
 * For further details on product contact nearest Legrand Sales Office.

Bold Cat.Nos are products normally available with Legrand (India) Stockists.
 Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.
 Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

DX³ MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Triple pole 415 V

4087 52	0.5	3	1666	1/32
4087 53	1	3	1666	1/32
4087 55	2	3	1666	1/32
4087 56	3	3	1666	1/32
4087 57	4	3	1666	1/32
4087 58	6	3	1314	1/32
4087 60	10	3	1314	1/32
4087 62	16	3	1314	1/32
4087 63	20	3	1314	1/32
4087 64	25	3	1314	1/32
4087 65	32	3	1314	1/32
4087 66*	40	3	2026	1/32
4087 67*	50	3	2026	1/32
4087 68*	63	3	2026	1/32

Triple pole + Neutral 415 V

4087 72	0.5	4	2088	1/32
4087 73	1	4	2088	1/32
4087 75	2	4	2088	1/32
4087 76	3	4	2088	1/32
4087 77	4	4	2088	1/32

Four pole 415 V

4087 78	0.5	4	2088	1/32
4087 79	1	4	2088	1/32
4087 81	2	4	2088	1/32
4087 82	3	4	2088	1/32
4087 83	4	4	2088	1/32
4087 84	6	4	1750	1/32
4087 86	10	4	1750	1/32
4087 88	16	4	1750	1/32
4087 89	20	4	1750	1/32
4087 90	25	4	1750	1/32
4087 91	32	4	1750	1/32
4087 92*	40	4	2524	1/32
4087 93*	50	4	2524	1/32
4087 94*	63	4	2524	1/32

Circuit breakers AC applications 80 - 125 A

10 kA as per IEC 60947-2
Integrated label holder
Sliding insulating shield
Color coded contact indication window
IP 20 protected terminals
50 sq mm terminals

Single pole 230 V / 400 V

4085 99	80	1.5	2046	1/5/160
4086 00	100	1.5	2292	1/5/161
4086 01	125	1.5	2474	1/5/162

Double pole 230 V / 400 V

4086 40	80	3	4534	1/5/60
4086 41	100	3	4838	1/5/60
4086 42	125	3	5318	1/5/60

Triple pole 400 V

4086 62	80	4.5	7148	1/9
4086 63	100	4.5	7618	1/9
4086 64	125	4.5	8452	1/9

Four pole 400 V

4087 03	80	6	9316	1/9
4087 04	100	6	9708	1/9
4087 05	125	6	10984	1/9

* MRP - Maximum Retail Price Inclusive of all taxes.
* For further details on product contact nearest Legrand Sales Office.

DX³ MCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Circuit breakers DC applications upto 63 A

6 kA as per IEC 60947-2
Integrated label holder
Sliding bottom clamp
Improved air channels
Color coded On/Off indication on dolly
Biconnect lower terminals
IP 20 protected terminals
Sliding shutters

Single pole 250 V

4087 98*	0.5	1	626	1/10/120
4087 99*	1	1	626	1/10/120
4088 01*	2	1	626	1/10/120
4088 02*	3	1	626	1/10/120
4088 03*	4	1	626	1/10/120
4088 04*	6	1	530	1/10/120
4088 06*	10	1	530	1/10/120
4088 08*	16	1	530	1/10/120
4088 09*	20	1	530	1/10/120
4088 10*	25	1	530	1/10/120
4088 11*	32	1	530	1/10/120
4088 12*	40	1	698	1/10/120
4088 13*	50	1	698	1/10/120
4088 14*	63	1	698	1/10/120

Double pole 250 V

4088 15*	0.5	1	1280	1/5/60
4088 16*	1	1	1280	1/5/60
4088 18*	2	1	1280	1/5/60
4088 19*	3	1	1280	1/5/60
4088 20*	4	1	1280	1/5/60
4088 21*	6	1	1120	1/5/60
4088 23*	10	1	1120	1/5/60
4088 25*	16	1	1120	1/5/60
4088 26*	20	1	1120	1/5/60
4088 27*	25	1	1120	1/5/60
4088 28*	32	1	1120	1/5/60
4088 29*	40	1	1410	1/5/60
4088 30*	50	1	1410	1/5/60
4088 31*	63	1	1410	1/5/60

DX³ isolators

Isolators for AC applications upto 125 A

ISI marked as per IEC 60947-3
Integrated label holder
Ergonomic red color dolly
Sliding bottom clamp
Double break mechanism
Improved air channels
Color coded On/Off indication on dolly
Biconnect lower terminals
IP 20 protected terminals
Sliding shutters

Double pole 240 V

4065 00	32	2	426	1/5/60
4065 01	40	2	468	1/5/60
4065 02	63	2	620	1/5/60
4065 04	100	2	842	1/5/60
4065 05	125	2	958	1/5/60

Triple pole 415 V

4065 09	32	3	762	1/40
4065 10	40	3	814	1/40
4065 11	63	3	964	1/40
4065 13	100	3	1076	1/40
4065 14	125	3	1244	1/40

Four pole 415 V

4065 18	32	4	838	1/32
4065 19	40	4	1040	1/32
4065 20	63	4	1138	1/32
4065 22	100	4	1402	1/32
4065 23	125	4	1544	1/32

Bold Cat.Nos are products normally available with Legrand (India) Stockists.
Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order.
Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.



4087 52



4088 12



4087 90



4086 00



4086 40



4086 63



4087 05



4065 00



4065 10



4065 20



DX³ RCCBs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

RCCBs for AC applications upto 63 A

ISI marked as per IS 12640-1
 Integrated label holder
 Ergonomic Grey color dolly
 Sliding bottom clamp
 Color coded On/Off indication on dolly
 Biconnect lower terminals
 IP 20 protected terminals
 35 sq mm terminals
 Sliding shutters

Double pole 240 V

30 mA

4118 51	25	2	2750	1/5/60
4118 52	40	2	3222	1/5/60
4118 53	63	2	3850	1/5/60

100 mA

4118 56	25	2	2964	1/5/60
4118 57	40	2	3440	1/5/60
4118 58	63	2	4086	1/5/60

300 mA

4118 61	25	2	3020	1/5/60
4118 62	40	2	3516	1/5/60
4118 63	63	2	4112	1/5/60

Four pole 415 V

30 mA

4118 76	25	4	3790	1/32
4118 77	40	4	3746	1/32
4118 78	63	4	4344	1/32

100 mA

4118 81	25	4	3932	1/32
4118 82	40	4	3956	1/32
4118 83	63	4	4670	1/32

300 mA

4118 86	25	4	4026	1/32
4118 87	40	4	4086	1/32
4118 88	63	4	4670	1/32

Four pole 415 V, A-S

300 mA

4118 91	25	2	5836	1/5/60
4118 92	40	2	6016	1/5/60
4118 93	63	2	6174	1/5/60
4118 94	80	2	7222	1/5/60

Double pole 240 V, HPI

30 mA

4118 71	25	2	5758	1/5/60
4118 72	40	2	6046	1/5/60
4118 73	63	2	6220	1/5/60
4118 74	80	2	7452	1/5/60

Four pole 415 V, HPI

30 mA

4118 96	25	4	6484	1/32
4118 97	40	4	6686	1/32
4118 98	63	4	6862	1/32
4118 99	80	4	8100	1/32

* MRP - Maximum Retail Price Inclusive of all taxes.

DX³ circuit breakers

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

AC applications upto 100 A

Integrated label holder
 Ergonomic Grey color dolly
 Color coded On/Off indication on dolly
 Biconnect lower terminals
 IP 20 protected terminals
 35 sq mm terminals
 Sliding shutters

Double pole 240 V

30 mA

4115 07	80	2	6434	1/5/60
4115 08	100	2	6992	1/5/60

100 mA

4115 17	80	2	6434	1/5/60
4115 18	100	2	6992	1/5/60

300 mA

4115 27	80	2	6434	1/5/60
4115 28	100	2	6992	1/5/60

Four pole 415 V

30 mA

4117 05	80	4	7552	1/32
4117 63	100	4	8034	1/32

100 mA

4117 15	80	4	7552	1/32
4117 73	100	4	8034	1/32

300 mA

4117 25	80	4	7552	1/32
4117 83	100	4	8034	1/32

DX³ RCBOs

RCBOs assembled for AC applications upto 63 A

ISI marked as per IS 12640-2
 Integrated label holder
 Ergonomic design
 Color coded On/Off indication on dolly
 Front face indication for earth leakage fault
 IP 20 protected terminals
 35 sq mm terminals
 Sliding shutters

Double pole 240 V, AC Type

30 mA

4113 22	6	4	3392	1/32
4113 23	10	4	3360	1/32
4113 24	16	4	3252	1/32
4113 25	25	4	3252	1/32
4113 26	32	4	3558	1/32
4113 27	40	4	4234	1/32
4113 28	63	4	5064	1/32

100 mA

4113 29	6	4	4184	1/32
4113 30	10	4	4184	1/32
4113 31	16	4	4026	1/32
4113 32	25	4	4026	1/32
4113 33	32	4	4026	1/32
4113 34	40	4	4634	1/32
4113 35	63	4	5362	1/32

300 mA

4113 36	16	4	4122	1/32
4113 37	25	4	4122	1/32
4113 38	32	4	4122	1/32
4113 39	40	4	4720	1/32
4113 40	63	4	5410	1/32

Bold Cat.Nos are products normally available with Legrand (India) Stockists. Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order. Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.

DX³ RCBOs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

Four pole 415 V, AC Type

30 mA

4113 88	6	7	4650	1/16
4113 89	10	7	4650	1/16
4113 65	16	7	4582	1/16
4113 66	25	7	4582	1/16
4113 67	32	7	4728	1/16
4113 68	40	7	4800	1/16
4113 69	63	7	5682	1/16

Four pole 415 V, AC Type

100 mA

4113 70	16	7	5120	1/16
4113 71	25	7	4898	1/16
4113 72	32	7	4952	1/16
4113 73	40	7	5096	1/16
4113 74	63	7	5790	1/16

Four pole 415 V, AC Type

300 mA

4113 75	16	7	5224	1/16
4113 76	25	7	5044	1/16
4113 77	32	7	5044	1/16
4113 78	40	7	5146	1/16
4113 79	63	7	5834	1/16



4113 79

RCBOs compact for AC applications upto 32 A, 6 kA

Conforms to IEC 60947
Integrated label holder
Ergonomic design
Color coded On/Off indication on dolly
Front face indication for earth leakage fault
IP 20 protected terminals
35 sq mm terminals
Sliding shutters

Double pole 240 V, AC Type

30 mA

4113 90	6	2	3948	1/32
4113 91	10	2	3948	1/32
4113 92	16	2	3948	1/32
4113 93	20	2	3948	1/32
4113 94	25	2	3948	1/32
4113 95	32	2	4146	1/32



4113 94

300 mA

4113 97	6	2	4060	1/32
4113 98	10	2	4060	1/32
4113 99	16	2	4060	1/32
4114 00	20	2	4060	1/32
4114 01	25	2	4060	1/32
4114 02	32	2	4266	1/32

Double pole 240 V, HPI Type

30 mA

4114 15	25	2	7572	1/32
4114 16	32	2	8004	1/32

* MRP - Maximum Retail Price Inclusive of all taxes.

DX³ RCBOs

Cat.Nos	Nominal Rating	Number of 17.5 mm modules	MRP* ₹ / Unit	Pack
---------	----------------	---------------------------	---------------	------

RCBOs compact for AC applications upto 32 A, 6 kA

Conforms to IEC 60947
Integrated label holder
Ergonomic design
Color coded On/Off indication on dolly
Front face indication for earth leakage fault
IP 20 protected terminals
35 sq mm terminals
Sliding shutters

Four pole 415 V, AC Type

30 mA

4111 85	10	4	5368	1/16
4111 86	16	4	5368	1/16
4111 87	20	4	5368	1/16
4111 88	25	4	5368	1/16
4111 89	32	4	5368	1/16



4111 88



4112 08

Four pole 415 V, AC Type

300 mA

4112 04	10	4	5924	1/16
4112 05	16	4	5924	1/16
4112 06	20	4	5924	1/16
4112 07	25	4	5924	1/16
4112 08	32	4	5924	1/16

Four pole 415 V, A Type

30 mA

4112 33	10	4	6056	1/16
4112 34	16	4	6056	1/16
4112 35	20	4	6056	1/16
4112 36	25	4	6056	1/16
4112 37	32	4	6056	1/16

Four pole 415 V, A Type

300 mA

4112 38	10	4	6490	1/16
4112 39	16	4	6490	1/16
4112 40	20	4	6490	1/16
4112 41	25	4	6490	1/16
4112 42	32	4	6490	1/16



4112 42

DX³ RCD add on module

For 125 A

Conform to IEC 61009-1
AC type : detect AC components faults
Hpi type : detect faults with AC and DC components, increased
Immunity to false tripping
For mounting on the right-hand side of 1.5 module per pole DX³ MCBs
Easy & fast association mechanism
Terminal cover for locking
70 sq mm terminals

Double pole 240 V, AC Type

30 mA

4105 68	125 A	4	11898	1
---------	-------	---	-------	---



4105 68

100 mA

4105 69	125 A	4	13412	1
---------	-------	---	-------	---

300 mA

4105 71	125 A	4	13412	1
---------	-------	---	-------	---

Bold Cat.Nos are products normally available with Legrand (India) Stockists. Cat.Nos that are not bold - delivery within 4 - 8 weeks from the date of order. Bold packing quantity is our mandatory packing. Orders to be placed by Legrand (India) Stockist in multiples of the same.