

MANIBHADRA ELECTRICALS PVT LTD						w.e.f 1st Jan-2017								
POWER CONTACTORS		3 POLE			RELAYS			ELECTRONIC KWH METERS						
		RATE			CAT NO.	RANGE	RATE	RATING	1 PHASE	3 PHASE				
TYPE	CAPACIT OR RANGE	CONTACTOR	KIT	COIL	DIRECTLY OPERATED MOUNTING			5-20A	1420	3410				
MNX9	6kVAr	775	490	440	MK1	Upto14A	765	10-40A		3510				
MNX12	7.5 kVAr	900	635	440	MK1	11 to 18 A	815	10-60 A DIR	1720	4310				
MNX18	9kVAr	1050	695	440	MK1	13 to 22 A	860	50-100 A DIR		6250				
MNX22	12.5 kVAr	1220	715	440	MN-2	Upto6-10A	1205	CT/5 -10 A		3810				
MNX25	15kVAr	1270	795	440	MN-2	9 to 15 A	1240	PLUS MVAT @ 12.5%						
MNX32	20 kVAr	2745	1485	440	MN-2	14 to 23 A	1440	PLUS MVAT @ 12.5%						
MNX40	20 kVAr	4230	2365	440	MN-2	20 to 33 A	2085	PLUS MVAT @ 12.5%						
MNX45	30 kVAr	6115	2745	1390	MN-2	24 to 40 A	2245	PLUS MVAT @ 12.5%						
CAPACITORS RATE PER KVAR														
MNX50	30 kVAr	6160	2805	1390	MN-5	9-15 & 14-23	2510	KVAR	STD DUTY	HEAVY DUTY	GAS FILLED	ULTRA HEAVY		
					MN-5	20 to 33 A	2530							
MNX70	35 kVAr	8280	4040	1390	MN-5	30 to 50 A	2730	440V	1 TO 25	5 TO 15	5 to 25	5 to 25		
					MN-5	36 to 60 A	3170							
MNX80	40 kVAr	10530	5445	1390	MN-5	45 to 75 A	3610	Cylindrical	186	331	331	672		
MNX95	65 kVAr	13240	6190	2360	MN-5	66 to 110 A	4155							
MNX110	65 kVAr	15950	7945	2360	MN-12	42-69 to 90-150 A	6405	Box Type	254	406				
MNX140	70 kVAr	21050	11215	2360	MN-12	135-225 A	7415							
MNX185	110kVAr	25325	12215	4250	MN-12	180 to 300 A	8105							
MNX 225	125kVAr	27880	13870	4250	MN-12	270 to 450 A	9265							
MNX 250	125kVAr	31450	16675	4250	ADD ON AUXILIARY CONTACT BLOCKS									
MNX 265	150kVAr	37100	18570	4950	Contacto Type	1 NO + 1 NC	2No+2NC	PLUS MVAT @ 5%						
MNX 300		37920	19520	4950	MNX 9 to 40	300	450	PLUS MVAT @ 5%						
MNX 325	175kVAr	42200	22545	4950	TRIPPER ELCB + MCB			TRIPPER ELCB + MCB (Earth Leakage Circuit Breaker + Miniature Circuit Breaker) Marketed in India by LARSEN & TUBRO LTD.						
MNX 400	175kVAr	48215	26855	4950										
MNX 550	250 kVAr	69145	35410	14675	AMP			2 POLE		4 POLE				
MNX 650	300 kVAr	103470	52200	14675	SENSITIVITY			30 MA	100/300 MA	30 MA	100/300 MA			
ML 1.5	(4P)5.5 HP	1105			6 A to 25 A			2745.00	2850.00	3455.00	3265.00			
ML 2		2530	1415	590	32 A to 40 A			3090.00	3030.00	3605.00	3455.00			
ML 3		4700	2305	980	63 A			3785.00	3620.00	4365.00	3990.00			
ML 4		6935	3880	980										
ML 6		11345	6050	1875										
ML 10		17910	10650	1875										
ML 12		39560	21695	4225										
		40565	24900	4025										
MCCB's														
MOULDED CASE CIRCUIT BREAKERS CONFIRMING TO IS 13947 (PART-2)								TIMER & TIME SWITCHES						
RATING AMP'S	DU				RATING AMPS.	DH			DU 100 H		ET 100 TIMER		3275.00	
	KA	3 POLE	4 POLE		KA	3 POLE	4 POLE	3 POLE	4 POLE	GIC FM/1 QT BASE MTG/W		2230.00		
63 A	10	1680	UPTO 60 A		63A	25	5700	7190	30 KA	GIC 2ASD TO TIMER		1075.00		
100 A	10	1840	80/100 A		100 A	25	6150	8020	4490	5950				
125 A	10	2680	100/125 A		125 A	35	7340	8780	4800	6400				
100 A	18	3710		4740	DU 250			SPREADER TERMINAL						
125 A	18	4080		5300	160 A	36	8270	10060	ITEM		3 POLE	4 POLE		
	DU 250 C				200 A	36	10710	13820	DTH		DN1/DN2 250	1280	1555	
160 A	25	6310		7900	250 A	36	12310	15840	50 KA	3 POLE	DN3 400	2205	3170	
200 A	25	7420		9350	320 A	50	15800	19840	800 AMP	44160	DN3 630	2485	3720	
250 A	25	8270		10890	400 A	50	16140	20180						
D-SINE MCCB's Thermal Magnetic Release		(36 KA) TYPE - S		(50 KA) TYPE - H		ROTARY OPERATING MECHANISM (HANDLE)								
		STD Breaking Capacity		High BreakingCapaci		TYPE		OP. HANDLE		NEW EXTENDED		DN 2 & DN 3		
TYPE	RANGE	3 POLE	4 POLE	3 POLE	4 POLE	DU 100		765.00		1460.00		DN2 DIRECT		1135
DN2-250	100-125	10500	12900	13170	17400	DU 250/250C		1055.00		1510.00		DN2		1760
	125-160	13680	16250	16490	19910	DU 100 H		990.00		1500.00		Extended		
	160-200	19300	23520	21590	26990	DH 3 Pole 125/160/200				1215.00		DN3 DIRECT		1700
	200-250	21000	25660	23210	28680	DU/DH/DL/DM 3 & 4				1450.00		DN3 Extended		2855
DN3-400	250-320	23930	30050	27620	34130	POLE 100/125/160/200				1450.00				
	320-400	24430	30540	27710	34600	DH 630 (DIRECT)		1270.00		2585.00		DTH 250/400		2565
DN3-630	400-500	28830	36730	31340	40550								DTH 630/800	2655
	500-630	31700	39520	33930	43440									